

3005 Cavity Coat Spray, Cavity Protection

Ver.: 2014-11

Description

Protective coating based on special waxes. High melting point prevents draining off at higher summer temperatures.


Features & Benefits

Strong adhesion
 Penetration into all vehicle cavities
 Anti corrosive protection
 Long-term noise protection

Substrate preparation

Surfaces to be treated must be clean, dry, rust-free and grease-free.

Application data



Mixing ratio

The product is ready to use!



Application

Shake the can thoroughly until the mixing balls move freely.

2 – 3 coats

Spraying distance 25 - 30 cm

Dry film thickness 250 - 500 micron

Application air temperature 15 - 20 °C

After spraying turn the can upside down and spray until the valve is clean. It is strongly recommended that ready to use product is applied at a temperature above 15°C.

3005 Cavity Coat Spray, Cavity Protection

Ver.: 2014-11



Drying

at 20°C

120 min

Prod. Nr.	Description	Volume	Packaging Box
3005	Transparent/White	500 ml	12

VOC

(2004/42/II B(e)(840)615

Shelf life

Min. 24 months from the production date under normal storage conditions and unopened can.

Additional Information

FOR PROFESSIONAL USE ONLY!

Always read the instructions.

IMPORTANT: This product contains hazardous substances at work so it is necessary to always use/wear appropriate protective equipment. For further instructions, check the label on the product and safety data sheet. A person who uses the product for any purpose other than recommended in this technical data sheet, acts at his own risk. It is the user's responsibility to take all necessary steps to fulfil the local legislation.

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public.

Information and methods described are based on the best information and practices known to us and serve merely as guidelines for optimal use, without liability to performance, results or fitness for any intended use. We do not accept any responsibility for the behaviour of the product or damage arising from the use of the product. Before using the product, the user must check if this is the latest version.

All products mentioned in this data sheet are trademarks owned by Silco.